deepnet
Deep Networks Poland

OPTIC FIBER PATCHCORD DROP, CORNING® SMF-CLEARCURVE LBL

DESIGNED FOR INDOOR/OUTDOOR USE

Application

Optic fiber Patchcord Drop is composed of a fiber optic cable FDE S-QOTKSdD, terminated with different connectors on the ends.
In this type of cable, Corning® SMF-ClearCurve LBL SM G.657A2 optical fiber is used in a tight buffer surrounded by aramid yarns.
The tight buffer layer provides excellent protection to individual optical fibers and prevents physical damage, bending, and stress on the fibers. The sheath is made of flame retardant, low smoke, halogen-free compounds with UV resistance.





Advantages

- Corning® SMF-ClearCurve LBL fiber G.657A2
- Optical fiber is protected in a tight buffer 0.9mm
- Reinforced with aramid yarns
- 3mm diameter
- High elasticity
- UV resistant LSZH sheath
- Completely dielectric
- Crushing resistance 0.8kNs

PRODUCT FEATURES

- Manufacturer: SteelNet
- Length: 10-1000m
- Fibre Quantity: 1 (Simplex)
- Connector Type: 1 side SC/APC, SC/UPC, LC/APC, LC/UPC
- Connector Type: 2 side SC/APC, SC/UPC, LC/APC, LC/UPC

Insertion Loss: ≤ 0.15 dB Return Loss: UPC ≥ 50 dB, APC ≥ 60 dB



STANDARDS

IEC 60794-1-1, IEC 60794-1-2, IEC 60794-3-20

Thank you for your cooperation!

Deepnet Europe Sp. z o. o.
KRS: 0000928596 , NIP / VAT number: 8222389646 , Regon: 520257080

Polska, 05- 300, Mińsk Mazowiecki, ul. Szczecińska 16 G

info@deepnet.pl
www.deepnet.pl